

# ENDURO-BASED Products Comparison Chart

Product System	Partition thickness	Vertical Framework		Horizontal Frame work		Reinforced Cover Configuration	Raceway Cover		Raceway Core	Partitions Panel & Overlays		Panel clip	A-Justable - Foot	Forged End Cap	Track System	Add-On panel Capabilities
		High Tolerance Aluminium Extrusion	Powder Coating Finished	High Tolerance Aluminium Extrusion	Mel Finished	High Tolerance Aluminium Extrusion	High Tolerance Aluminium Extrusion	Hinged assembly Locking System	Panel material	Inter-changeable panel						
<b>X-65 Tile</b>	65 mm	1.5-2mm Thickness	Powder Coating Finished	1.5-2mm Thickness	Mel Finished	Powder Coating Finished	W: 2mm H: 120 mm	Powder Coating Finished	Mel Finished	Particle Board or MDF 9mm	●	Water Resistant NYLON transparent panel	Water Resistant NYLON transparent panel	High grade aluminium die-cast	Horizontal Track assemblies	●
<b>X-65 Solid</b>	65 mm	1.5-2mm Thickness	Powder Coating Finished	1.5-2mm Thickness	Powder Coating Finished	Powder Coating Finished	W: 2mm H: 120 mm	Powder Coating Finished	Mel Finished	Plywood 3mm	●	-	Water Resistant NYLON transparent panel	High grade aluminium die-cast	-	●
<b>SLIMMO</b>	35 mm	1.5-2mm Thickness	Powder Coating Finished	1.5-2mm Thickness	Mel Finished	Anodize or Powder Coating Finished	W: 2mm H: 120 mm	Anodize or Powder Coating Finished	Mel Finished	Plywood 3mm	●	-	Water Resistant NYLON transparent panel	High grade NYLON die-cast	Horizontal Track assemblies	●
<b>VISIO</b>	50 mm	1-1.5mm Thickness	Powder Coating Finished	1.5-2mm Thickness	Mel Finished	Powder Coating Finished	W: 1mm H: 90 mm	Powder Coating Finished	Mel Finished	Plywood 3mm	●	-	Water Resistant NYLON transparent panel	High grade PVC die-cast	-	●

- Note :
- All Frameworks are accurately extruded Aluminium alloy 6063, tensile strength shall be T-5 (minimum 38,000 psi).
  - ENDURO products show its commitment to provide quality service, support and products to our custo rs by being ISO 9001:2000 certified.